

Plasterboard faced door within a 50mm deep beaded frame

Non Fire Rated

APPLICATION

This unit's frame and door are designed to be taped and jointed/skimmed when fitted within plasterboard lined applications for metal track systems, timber stud/joists or concrete blockwork.



DESCRIPTION

This access panel has a plasterboard faced beaded door and is supplied with a beaded frame for plaster skim on site to fully conceal the access panel. The panel has a simple hinge system for ease and speed of assembly on site with pin location on one side and one screw fitting on the other. The panel is fitted with a **budget lock** as standard, but other locking options are available.

MATERIALS & FINISHES

Intrepid access panels are manufactured from 1.2mm thick Zinc plated mild steel (BS EN 10025) for maximum rigidity. Stainless steel finishes are also available.

The Access panels are painted in a polyester powder coating (BS EN 12206-1:2004) – White - RAL 9010 textured, as standard. This paint texture blends well with your plastered painted walls and can be overpainted with ease. Other colours are available to match your finished area.

SIZING	PANEL SIZE	STRUCTURAL OPENING	CLEAR OPENING WITH DOOR OPEN
EXAMPLE	600 x 600	610 x 610	576 x 573
FORMULA	Height	+ 10	- 24
	Width	+ 10	- 27

All measurements shown in the above table are in mm.

Note: Largest door in this range would be 1200mm x 600mm.



RATING

This panel construction has not been tested.

OTHER LOCK TYPES AVAILABLE

- Standard key lock
- Castellated tamperproof lock

INSTALLATION

Intrepid supply installation instructions in the form of labels on the rear of the doors. The label will have the relevant certification standard that it complies to clearly marked. As part of our quality system, you will also find on the label, the identity mark of the quality inspector, who has done the final checks on your product.



Intrepid Manufacturing Limited
Whitacre Road Industrial Estate
CV11 6BP

Company Reg: 07769855
VAT Reg: GB120669918

