

Circular - plasterboard faced door within a 50mm deep beaded frame

Non Fire Rated

APPLICATION

This unit's frame and door are designed to be taped and jointed/skimmed when fitted within plasterboard lined applications for metal track systems or timber joist ceilings.



DESCRIPTION

This access panel has a plasterboard faced door and is supplied with a beaded frame. The panel has a simple hinge system for ease and speed of assembly on site with pin location in the frame and a bayonet fitting in the door. The door is also fitted with safety wires as standard to remove the door safely away from the frame.

MATERIALS & FINISHES

Intrepid access panels are manufactured from 1.2mm thick Zinc plated mild steel (BS EN 10025) for maximum rigidity. Stainless steel finishes are also available.

The Access panels are painted in a polyester powder coating (BS EN 12206-1:2004) – White - RAL 9010 textured, as standard. This paint texture blends well with your plastered painted walls and can be overpainted with ease. Other colours are available to match your finished area.

SIZING	PANEL SIZE	STRUCTURAL OPENING	CLEAR OPENING WITH DOOR OPEN
EXAMPLE	600	610	600
FORMULA		+ 10	

All measurements shown in the above table are in mm.

Note: Largest circular door in this range would be 600mm Dia.



RATING

- This panel construction has not been tested.
- Not suitable for use in walls.

INSTALLATION

Fixing points are pre-punched in the frames for fixing. The circular hole will need supports to the ceiling to fix the access panel to.