

Decorative board panel with 7mm surround

Non Fire Rated

APPLICATION

This panel is designed to be fitted within timber stud/ joists, concrete blockwork or metal track systems.



DESCRIPTION

This access panel has been designed to accept a decorative board on site. The door and frame have a 7mm lip to conceal the cut edges of the decorative board. One edge of the door is removable to allow the board to slide in. The panel is fitted with a standard **budget lock** and operates on a pivot hinge so it can be easily removed and refitted for simple installation.

MATERIALS & FINISHES

Intrepid access panels are manufactured from 1.2mm thick Zinc plated mild steel (BS EN 10025) for maximum rigidity. Stainless steel finishes are also available.

The Access panels are painted in a polyester powder coating (BS EN 12206-1:2004) – White - RAL 9010 textured, as standard. This paint texture blends well with your plastered painted walls and can be overpainted with ease. Other colours are available to match your finished area.

SIZING	PANEL SIZE	STRUCTURAL OPENING	CLEAR OPENING WITH DOOR OPEN
EXAMPLE	600 x 600	610 x 610	576 x 561
FORMULA	Height	+ 10	- 24
	Width	+ 10	- 39

All measurements shown in the above table are in mm.

Note: Smallest door unit is 300mm x 300mm, Largest door unit is 600mm x 600mm.



RATING

- This panel construction has not been tested.
- Not suitable for use in walls.

OTHER LOCK TYPES AVAILABLE

- 5mm bit insert into budget locking
- Touch Latch

INSTALLATION

Intrepid supply installation instructions in the form of labels on the rear of the doors. The label will have the relevant certification standard that it complies to clearly marked. As part of our quality system, you will also find on the label, the identity mark of the quality inspector, who has done the final checks on your product.



Intrepid Manufacturing Limited
Whitacre Road Industrial Estate
CV11 6BP

Company Reg: 07769855
VAT Reg: GB120669918

