

Metal faced door within a 28mm deep picture frame

Non Fire Rated - Air Sealed - Acoustic Rated 29dB

APPLICATION

This unit's frame is designed to be fitted within plasterboard lined applications for metal track systems, timber studs/joists or concrete blockwork.



DESCRIPTION

This access panel has a metal faced door and is supplied with a picture frame. The panel has a simple pivot hinge system for ease and speed of assembly on site. The panel is fitted with a **budget lock** as standard, but other locking options are available.

MATERIALS & FINISHES

Intrepid access panels are manufactured from 1.2mm thick Zinc plated mild steel (BS EN 10025) for maximum rigidity.

Stainless steel finishes are also available.

The Access panels are painted in a polyester powder coating (BS EN 12206-1:2004) – White - RAL 9010 textured, as standard. This paint texture blends well with your plastered painted walls and can be overpainted with ease. Other colours are available to match your finished area.

SIZING	PANEL SIZE	STRUCTURAL OPENING	CLEAR OPENING WITH DOOR OPEN
EXAMPLE	600 x 600	610 x 610	576 x 564
FORMULA	Height	+ 10	- 24
	Width	+ 10	- 36

All measurements shown in the above table are in mm.

Note: Largest door in this range would be 1200mm x 600mm.

RATING

- Tested to BS EN ISO 10140-2 for acoustic performance, giving an Rw29dB sound reduction rating.
- Tested to BS EN 1026:2000 for air leakage and classified as Class 2.

OTHER LOCK TYPES AVAILABLE

- 5mm bit insert into budget locking
- IP65 tamperproof insert into budget locking

INSTALLATION

Intrepid supply installation instructions in the form of labels on the rear of the doors. The label will have the relevant certification standard that it complies to clearly marked. As part of our quality system, you will also find on the label, the identity mark of the quality inspector, who has done the final checks on your product.



Intrepid Manufacturing Limited
Whitacre Road Industrial Estate
CV11 6BP

Company Reg: 07769855
VAT Reg: GB120669918

